

Emergency Aid Camp Infrastructure Family Water Filter



Flow Rate:

2 litres per minute*

Ultrafiltration Filter Capacity:

200,000 litres*

Operating Life:

>5 years*

Bacteria Retention:

>99,9999% (log 6)

Virus Retention:

>99,99% (log 4)

MWCO:

100,000 Daltons (equivalent to 0.01 Microns)

US Compliance:

EPA-US National Primary Drinking Water Regulations under the Safe Water Drinking Act 93-523

Normal Operational Turbidity

Range:

0 - 50 NTU

Dimensions of Packaged System:

Height: 360mm

Width: 80mm

Depth: 150mm

Units per Pallet:

Standard Pallet 270

Euro Pallet 180

To Operate:

1. Collect water in a bucket or any other available vessel
2. Place the Grifaid® Family Filter in the water
3. Pump for safe drinking water



Dry Weight:
1.2kg

Design Features:

- Detachable pre-filter gauze
- 120 microns mesh screen
- Automatic cross flow cleaning
- Built-in back flushing
- Built-in purging

Maintenance:

- Stored-in grease reservoir
- Stored-in spare seals

Pressure Control:

- 3.5 Bar security valve

Warranty:

1 year international limited



Butyl Products Ltd.

Lingfield House, 11 Radford Crescent, Billericay, Essex,
CM12 0DW, United Kingdom. T: +44 (0) 1277 653 281

E: enquiries@butylproducts.co.uk W: butylproducts.co.uk